

## Maintenance

### ALUMINIUM SURFACES

Aluminium has a natural beauty and luster. Its surface can be treated in various ways to produce different effects, while in the hands of the skilled architect it lends itself to some excellent effects and variations, and contrasts with other materials. For this reason and because aluminium is so well-proven in service, it is now by far the most common material for exterior work such as windows, doors, curtain walls and shop fronts.

The surface finish of aluminium can be spoiled by improper care and the purpose of this note is to summarize the methods of maintaining aluminium after proper installation on site.

Endurawood substantially enhances appearance and renders the surface more resistant to various forms of attack and facilitates cleaning and maintenance.

Grime which causes deterioration cannot be prevented from settling on exposed surfaces. If cleaned reasonably frequently then the mildest methods of washing will produce satisfactory results.

There are many ways to clean aluminium, from using plain water to harsh abrasives. The type of cleaning that should be used is governed by the finish, degree of soiling, and the size, shape and location of the surface to be cleaned. Regular cleaning of the surface with the correct materials will ensure an everlasting product.

The mildest method possible should be used. The following cleaning materials and procedures are listed in ascending order of harshness. The mildest treatment should be tried on a small area and if not satisfactory only then should the next item be examined.

- Plain water
- Mild soap or detergent
- Solvent cleaning, e.g. kerosene, turpentine, white spirit
- Non-etching chemical cleaner
- Wax base polish cleaner
- Abrasive wax
- Abrasive cleaner

After applying the cleaner, aluminium should be washed down thoroughly and dried with a clean cloth to prevent streakiness. There should be no concentration of the cleaner at the bottom edges of the aluminium. If using proprietary cleaners, the maker's recommendation should be obtained and followed carefully.

If abrasives are used, then the appearance of the aluminium finish may be altered. If there is a grain in the finish then cleaning should always be with the grain.

Once the condition of the surface requires the use of abrasive or etching materials it is advisable to consult either cleaning specialists, or Endurawood's Technical Service Department will be pleased to offer advice.